

Pura Soft+

Premium Softener + Whole Home Taste & Odor Filter



Get the best of both worlds – luxuriously soft water and less chlorine and chloramines – with this premium all-in-one system. It's designed to use minimal salt and water, so you'll save money and carry fewer bags of salt while enjoying years of soft, filtered water from every tap in your home.

Upflow Regeneration

Uses salt more efficiently by only recharging the part of the softening bed that needs it - no waste and fewer salt refills.

Precision Brining

Mixes just the right amount of brine every time—helping you use up to 30% less salt.

Automatic System Refresh

No water use for a while? No problem. The system gives itself a gentle refresh after 7 days to help prevent bacteria.

Backwash Frequency Preset

Live on clean municipal water? You can save up to 2,000 gallons of water per year by skipping up to ten backwash cycles per year.

Premium Carbon Filtration

Catalytic carbon reduces chlorine, chloramines, and other contaminants for cleaner, fresher water.

Soft Water Recharge

Running low? If softening capacity dips below 3%, the system automatically gives itself a quick 15-minute boost to keep the soft water flowing.

Tank Features

Includes a safety float, air check and sturdy brine grid to prevent salt bridging.



1" porting for large homes and high demand water use

Distributed by:


BLUE WOLF
CONCEPTS
your water treatment experts

Pura Soft+

Product Specifications



Model	Pura Soft Plus 1.0	Pura Soft Plus 1.5
Item #	19050002	19050003
Hardness Removal (Grain Capacity)		
@ 10 LBS	22,500	40,000
@ 6 LBS (Factory Setting)	18,750	31,250
@ 3 LBS	11,250	18,750
System Specifications		
Water Used Per Regeneration (Municipal)	86.4 gal	148.0 gal
Salt Used Per Regeneration	6.0 lbs	9.0 lbs
Softener Resin (Cubic Feet)	0.8 ft3	1.2 ft3
Carbon (Cubic Feet)	0.2 ft3	0.3 ft3
Tank Size	9 x 48	10 x 54
Media Loaded	Yes	Yes
Salt Storage Capacity	270 lbs	270 lbs
Service Flow Rate	10.0 USGPM	12.0 USGPM
Back Wash Flow Rate	2.0 USGPM	2.4 USGPM
Shipping Weight	110 lbs	141 lbs
Regeneration Type	Upflow	
Plumbing Connections	Includes 1" 90° elbows NPT	
Resin Type	High Capacity Ion Exchange Resin	
Carbon Type	Catalytic Carbon	
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA	
Water Temperature	Min 39 - Max. 100° F	
Water Pressure	Min. 20 - Max. 125 psi	
DIMENSIONS	Pura® Soft Plus -1.0	Pura® Soft Plus -1.5
Tank & Valve (A x B)	57" x 9"	63" x 10"
C x D (Inches)	19" x 35"	19" x 35"



"Pura makes buying a water softener super easy and affordable. No high pressure sales tactics. I had a brand new water softener, within 48 hours, professionally installed by a very efficient and professional installer. Pura's customer focused model is exceptional. This was one of the best service experiences I've had."

Certified Performance



Pura systems are tested and certified by IAPMO, a global leader in protecting public health through standards development and product testing.

Warranty



Distributed by:
Blue Wolf Concepts
465 N Cedar Road
Mason, MI 48854
517.992.5065

